Basic Features - DPM-2000 Series

- Pressure Ranges:
 - 13.50 to 100.00 PSI
 - 698 to 5171 mmHg
 - 950 to 7037 cm H₂O
 - 374 to 2771 inches H₂O
- ♦ 0.1% FS Pressure Accuracy
- 5 Digit LCD Display
- Programmable Digital Filter
- Digital Calibration & Zero Adjust
- Male Luer Connector
- Small self contained package (7" x 4" x 1.5")
- ♦ Battery Life Display (0 to 100%)

Features - DPM-2001PLUS

- Has all of the features of the DPM-2001, PLUS:
 - Min/Max Pressure Value Capture
 - RS232 Serial Communications

Features - DPM-2100

- Has all of the features of the DPM-2001, PLUS:
 - YSI 700 Temp Probe Interface
 - +32.0° to +212.0°F Temp Range
 - 0.5% FS Temp Accuracy
 - Min/Max Temp Value Capture
 - Min/Max Pressure Value Capture
 - RS232 Serial Communications

BC Group International, Inc. 3081 Elm Point Industrial Dr. St. Charles, MO 63301 USA

Phone: 314-638-3800 Toll Free: 1-888-223-6763

Fax: 314-638-3200

Email: sales@bcgroupintl.com
Website: www.bcgroupintl.com

DIGITAL PRESSURE METERS

BC Biomedical DPM-2000 Series



This microprocessor based series of meters offers not only positive & negative pressure sensing of compatible liquids & gases, but also has models that offer Temperature & RS232.

All of the BC Biomedical DPM-2000 models measure positive and negative pressure, and are compatible with both liquid and gases. The DPM-2001 is the base model. The DPM-2001 PLUS adds a "Min/Max" feature plus an RS-232 port. The top-of-the-line DPM-2100 is a pressure/temperature meter. It has all the features of the PLUS model and also includes a YSI 700 temperature probe interface.

Each model has a battery life display (0 to 100%), LCD contrast is software adjustable, digital calibration-no pots to turn, .1% of full scale accuracy, -13.50 to 100.00 PSI range, digital zero adjust, and four pressure scales: PSI, inH₂O, cmH₂O and mmHG.



BC BIOMEDICAL DPM-2000 SERIES

SPECIFICATIONS

Pressure Ranges

 $\begin{array}{lll} \text{PSI} & -13.50 \text{ to } 100.00 \\ \text{mmHg} & -698 \text{ to } 5171 \\ \text{cm H}_2\text{O} & -950 \text{ to } 7037 \\ \text{inches H}_2\text{O} & -374 \text{ to } 2771 \\ \text{Pressure Accuracy} & .1\% \text{ F.S.} \end{array}$

Temperature Range

Temp Range 0.0° to 100.0° C (DPM-2100 Only)
Temp Accuracy .5% FS (DPM-2100 Only)

Electrical

Power 9V Alkaline Battery Battery Life (Cont. Hrs.) 90 (DPM-2100 is 80)

AC Adapter Yes

Mechanical

Pressure Connector Male Luer

Temp Connector YSI-700 1/4" Phone (DPM-2100 Only)

Size 7" x 4" x 1.5"
Weight 0.8 lbs
Max Pressure 120 PSI

Other Specs

Display LCD, 5 Characters, .35" High Enclosure ABS Plastic, with Built-In Stand

Min/Max Capture Yes (DPM-2001 PLUS & DPM-2100 Only) RS232 Yes (DPM-2001 PLUS & DPM-2100 Only)

DC Output No

DPM-2000 MODEL SUMMARY

BC Model Description
DPM-2001 Basic Unit

DPM-2001PLUS Basic Unit + Capture & RS232

DPM-2100 Basic Unit + Capture, RS232 & Temp

Optional Accessories

BC20-21100 120V Battery Eliminator (U.S.)
BC20-21101 220V Battery Eliminator (European)
BC20-21102 RS232 Communications Cable

BC20-30106 Soft Carrying Case

BC Group International, Inc. 3081 Elm Point Industrial Dr. St. Charles, MO 63301 USA

Phone: 314-638-3800 Toll Free: 1-888-223-6763

Fax: 314-638-3200

Email: sales@bcgroupintl.com
Website: www.bcgroupintl.com

